

CANADA PIPELINE ACCESSORIES (1986) CORP.

Style SC-2 All-Stainless Steel Saddle Clamps

Canada Pipeline's saddle clamps with their one piece construction, make installation quick and easy. The extra wide stainless shell assures equal pressure around the circumference of the pipe. This extra wide support is particularly important when tapping PVC or Polyethylene pipe.

A key feature of our saddle design is the encapsulation of the sealing gasket to ensure optimum performance.

SS Tapping Saddle - Material Specifications

Bolts 18-8 stainless steel, 5/8" roll NC thread in

sizes 4" and larger.

Bolt & receiver

304 stainless steel. TIG welded to shell to form a strong fusion,

Bars

Shell

and fully passivated.

Locking washer

304 stainless steel.

Plate

304 stainless steel. Locks into position for easy tightening of nuts.

Nuts

18-8 stainless steel & fluorokote coated.

Washer

Nylon and stainless steel washers used to reduce wear on washer

plate.

Gasket

SBR Rubber - ASTM D 2000 AA4 15 rubber is specially

formulated for water service.

STYLE SC-2 DOUBLE BOLT SADDLE CLAMP

1-1/4", 1-1/2" & 2" FMI & CC				
NOMINAL	O.D.	CATALOG	WIDTH	WEIGHT
SIZE IN	RANGE	NUMBERS	IN	EACH
INCHES	INCHES		INCHES	LB.
*3"	3.40-3.65	SC2-0365-TAP	5"	3
4"	4.45-4.85	SC2-0485-TAP	7-1/2"	3
4''	4.95-5.35	SC2-0535-TAP	7-1/2"	3
6"	6.54-7.00	SC2-0700-TAP	7-1/2"	5
6"	6.99-7.45	SC2-0745-TAP	7-1/2"	5
8"	8.63-9.08	SC2-0908-TAP	7-1/2"	6
8"	9.21-9.67	SC2-0967-TAP	7-1/2"	6
10"	10.70-11.16	SC2-1116-TAP	7-1/2"	6
10"	11.75-12.21	SC2-1221-TAP	7-1/2"	6
12"	12.74-13.21	SC2-1321-TAP	7-1/2"	7

^{* 3&}quot; available only 1-1/4, 1-1/2 FMI & 1-1/4 CC

All stainless material fully passivated Torque bolts to 60 FT.LBS

Page 1