





The Palintest Chlorometer Duo provides a convenient, accurate and easy-to-use photometer capable of providing on-the-spot confirmation of both disinfectant and residual protection chlorine levels.

The Palintest CHLOROMETER DUO 1000 offers water utilities a new dimension in chlorine testing.

Used in conjunction with the Palintest DPD Chlorine method, it provides a simple means of accurately measuring chlorine residuals. It can also be used with Palintest high range Chlorine HR test tp provide a fast check on disinfection and sterilization levels in pipework.

CHLOROMETER DUO 1000 - SPECIFICATIONS

0-200mg/I RANGE 1 mg/l Cl

PULSED LED COLORIMETER PRE-PROGRAMMED FOR DIRECT READING OF CHLORINE

DUAL RANGES: 0.00 - 5.00 mg/l (Chlorine DPD)

0-200mg/l (Chlorine HR)
 RESOLUTION 0-5mg/l RANGE 0.01 mg/l Cl

. EASY READ 10 mm LCD DISPLAY

. TWO BUTTON OPERATION FOR EASY USE

. AUTOMATIC BLANK RECOGNITION

RANGE SETTING MEMORY

FACTORY SET MULTIPOINT CALIBRATIONS

SPLASH PROOF CASE WITH FULLY SEALED CELL HOLDER

 POWER MANAGEMENT SYSTEM WITH AUTO SWITCH OFF GIVES APPROX 20,000 READINGS FROM 2 x 1.5v BATTERIES

PRODUCT ORDERING INFORMATION

PT227 Chlorometer Duo supplied in soft carry pouch

PT238 Optional hard carry case

PT233/M2 Check standard with test certificate
AP031 DPD No. 1 & 3 tablets (pack of 250)
AP162 Chlorine High range (pack of 250) test

3x2 Type 'A' Adapter

The 3x2 adapter is all you need, If your requirements call for connections less then 2 ½ NST.





Special Type 'A' adapter with 2 inch female threads